DEP7007 Forms (AI, A, N and V)

11/2018 DEP7007AI

Division for Air Quality		Duality		DEP7007AI	Additional Documentation			
300 Sower Boulevard Frankfort, KY 40601 (502) 564-3999		Sectio Sectio Sectio Sectio	istrative Information AI.1: Source Information AI.2: Applicant Information AI.3: Owner Information AI.4: Type of Applicat	Addit	ional Documentation attached			
			Sectio	on AI.5: Other Required In on AI.6: Signature Block on AI.7: Notes, Comment		ations		
Source Name:		<b>Buffalo Tra</b>	ce Distillery, Inc.					
KY EIS (AFS) #	<b>#:</b>	21-073-0000	9					
Permit #:		V-12-056						
Agency Interest	(AI) ID:	1373						
Date:		9/25/2019						
Section AI.1	l: Source I	nformation						
Physical	Street:	113 Great Bu	ıffalo Trace					
Location Address:	City:	Frankfort		County: Franklin		Zip Code:	40601	
Mailing	Street or P.O. Box:	Same as phys	sical address					
Address:	City:			State:		Zip Code:		
			Standard Coordin	nates for Source Physica	al Location			
Longitude:		-84.871° E	(decimal degrees)	Latitude: _	38.2166	94° N	(decimal degrees)	
Primary (NAICS	S) Category:	Distilleries		Primary NA	AICS #: 31	2140		

EP7007AI Classification (SIC) Category: Distilled and Blended Liquors 2085 **Primary SIC #:** The site produces distilled spirits. Grain is delivered, ground, and introduced to mash cookers. The mash is fed to fermenters and then to Briefly discuss the type of business distillation columns and condensers. The resulting liquid is stored in tanks, transferred to barrels for aging, and/or sent to the bottling area for conducted at this site: packaging. Barrels of bourbon are stored in rick houses for aging. The spent grain is sold as distiller's dried grain. Beverage ingredients are received in bulk for blending, and other distilled spirits are received by the facility in bulk and sent to the bottling area for packaging. **Description of** Rural Area ☐ Industrial Park Residential Area Yes Is any part of the source Number of 474 Area located on federal land? **Employees:** ✓No ☑Commercial Area Urban Area ☐ Industrial Area Surrounding Approximate distance to nearest residence or **Property** 430 Acres Is this source portable? Yes 🗸 No commercial Adjacent Area: What other environmental permits or registrations does this source currently hold or need to obtain in Kentucky? Currently Hold NPDES/KPDES: N/A Need Currently Hold ✓ N/A **Solid Waste:** Need Currently Hold ✓ RCRA: Need N/A Currently Hold ✓ N/A UST: Need ☐ Mixed Waste Generator Other: Type of ☑ Generator Recycler **Regulated Waste Activity:** Transporter ☐ Treatment/Storage/Disposal Facility U.S. Importer of Hazardous Waste N/A

11/2018

11/2018 DEP7007AI

Section AI.2: Ap	plicant Informatio	n									
Applicant Name:	Buffalo Trace Distiller	У				_					
Title: (if individual)											
Mailing Address:	Street or P.O. Box: 113 Great Buffalo Trace										
Wannig Address.	City:	Frankfort	State:	KY	Zip Cod(	40601					
Email: (if individual)											
Phone:	(502) 223-7641										
<b>Technical Contact</b>											
Name:	Andrew Leet										
Title:	Environmental Engine	er									
Mailing Address:		113 Great Buffa				_					
17 <b>2g</b> 12 6550	City:	Frankfort	State:	KY	Zip Code	40601					
Email:	aleet@buffalotrace.com	n				_					
Phone:	(859) 705-8187										
Air Permit Contact fo	or Source										
Name:	Andrew Leet										
Title:	Environmental Engine	er				_					
Mailing Address:	Street or P.O. Box:	113 Great Buffa	alo Trace								
maning radices.	City:	Frankfort	State:	KY	Zip Code	40601					
Email:	aleet@buffalotrace.com	n									
Phone:	(859) 705-8187										

DEP7007AI

Section AI.3: Ov	wner Information			
☑ Owner same	e as applicant			
Name:				
Title:				
Mailing Address:	Street or P.O. Box:			
Wanning Address.	City:	State:	Zip Code:	
Email:				
Phone:				
List names of owners a	nd officers of the company who h	nave an interest in the company of 5% or i	more.	
	Name		Position	
	Wholly-owned subs	sidiary of the Sazerac Company; New C	rleans, LA	
-		<del></del>		

11/2018 DEP7007AI

Section AI.4: Ty	pe of Application							
Current Status:	✓ Title V ☐ Conditional	Major State-On	rigin		General Permit	Registr	ration	☐ None
Requested Action: (check all that apply)  Requested Status:	Name Change   ✓ Renewal Permit   □ 502(b)(10)Change   □ Revision   □ Ownership Change   ✓ Title V   ☐ Conditional	Initial Registration Revised Registration Extension Request Off Permit Change Closure  Major	□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □	Significant Revision Addition of New Landfill Alternat	Facility te Compliance Submitt	☐ Initial S ☐ Portable ☐ Modifie	Source-wide ( e Plant Reloc	ting Facilities
Pollutant:	e Compounds (VOC) de	al emissions?  Requested Limit:			No utant: Single HAP Combined HAPs Air Toxics (40 CFR 68, Carbon Dioxide Greenhouse Gases (GHO)	Subpart F)	Requested L	imit:
_	rt Date of Construction: (MM/YYYY)			Proposed (	Operation Start-Up Da (MM/YYYY)	ate:		
Proposed Sta	s: rt Date of Modification: (MM/YYYY)			Proposed (	Operation Start-Up Da	ate:		
Applicant is seekir	ng coverage under a permit sh	hield. Yes			dentify any non-applic nield is sought on a sep			_

DEP7007AI

Section AI.5 Other Required Information								
Indicate the documents attached as part of this application:								
☐ DEP7007A Indirect Heat Exchangers and Turbines ☐ DEP7007B Manufacturing or Processing Operations ☐ DEP7007C Incinerators and Waste Burners ☐ DEP7007F Episode Standby Plan ☐ DEP7007J Volatile Liquid Storage ☐ DEP7007K Surface Coating or Printing Operations ☐ DEP7007L Mineral Processes ☐ DEP7007M Metal Cleaning Degreasers ☐ DEP7007N Source Emissions Profile ☐ DEP7007P Perchloroethylene Dry Cleaning Systems ☐ DEP7007R Emission Offset Credit ☐ DEP7007S Service Stations ☐ DEP7007T Metal Plating and Surface Treatment Operations ☐ DEP7007V Applicable Requirements and Compliance Activities ☐ DEP7007Y Good Engineering Practice and Stack Height Determination ☐ DEP7007AA Compliance Schedule for Non-complying Emission Units	DEP7007CC Compliance Certification DEP7007DD Insignificant Activities DEP7007EE Internal Combustion Engines DEP7007FF Secondary Aluminum Processing DEP7007GG Control Equipment DEP7007HH Haul Roads Confidentiality Claim Ownership Change Form Secretary of State Certificate Flowcharts or diagrams depicting process Digital Line Graphs (DLG) files of buldings, roads, etc. Site Map Map or drawing depicting location of facility Safety Data Sheet (SDS) Emergency Response Plan Other:							
responsibility for obtaining the information, I certify that the inform	attachments. Based on my inquiry of those individuals with primary							

Section AI.7: Notes, Comments, and Explanations	

DEP7007AI

11/2018

11/2018 DEP7007AI

# Division for Air Quality

300 Sower Boulevard Frankfort, KY 40601 (502) 564-3999

# **DEP7007A**

# Indirect Heat Exchangers and Turbines

 Section A.1: General Information
 Section A.2: Operating and Fuel Information
Section A.3: Notes, Comments, and Explanation

Additional	<b>Documentation</b>
------------	----------------------

\_\_\_ Complete DEP7007AI, DEP7007N, DEP7007V, and DEP7007GG.

Manufacturer's specifications

Source Name:	Buffalo	Trace	Distillery, 1	nc.

KY EIS (AFS) #: <u>21-073-00009</u>

**Permit #: V-12-056** 

Agency Interest (AI) ID: 1373

Date: 9/25/2019

### **Section A.1: General Information**

Emission Unit #	Emission Unit Name	Process ID	Process Name	Identify General Type: Indirect Heat Exchanger, Gas Turbine, or Combustion Turbine	Indirect Heat Exchanger Configuration	Manufacturer	Model No./ Serial No.	Proposed/Actual Date of Construction Commencement (MM/YYYY)	SCC Code	SCC Units	Control Device ID	Stack ID
15	BOILER 11	01	NATURAL GAS COMBUSTION	INDIRECT HEAT EXCHANGER	Industrial Watertube Boiler	CLEAVER BROOKS BOILER/ LIMPSFIELD BURNER	Burner: LCNOAL175/ 00514	2002	10200602	MMscf	NA	S15
15	BOILER 11	02	GNS COMBUSTION	INDIRECT HEAT EXCHANGER	Industrial Watertube Boiler	CLEAVER BROOKS BOILER/ LIMPSFIELD BURNER	Burner: LCNOAL175/ 00514	2002	10200502	Mgal	NA	S15

11/2018 DEP7007AI

# Section A.2: Operating and Fuel Information

Emission		ipurpose entage of		lentify the purpose	Rated Capacity	Rated (	Capacity Output	Describe Operating Scenario	Classify Fuel as Primary	Identify Fuel Type: Coal, Natural Gas, Wood, Biomass,		Content IHV)	Maximum	Ash	Sulfur
Unit #	Space Heat	Process Heat	Power	Emergency	Heat Input (MMBTU/hr)		(Specify units: hp, MW, or lb steam/hr)	(only if this unit will be used in different configurations)	or Secondary	Landfill/Digester Gas, Fuel Oil # (specify 1-6), or Other		(Specify units: Btu/lb, Btu/gal, or Btu/scf)	Operating Hours	(%)	Content (%)
15					60.5	Unk			Primary	Natural Gas	1,020	Btu/scf	8,760	N/A	N/A
15					60.5	Unk			Secondary	GNS	69,095	Btu/gal	8,760	N/A	N/A
									_						
															<b></b>

1	1	12	Λ	1 Q

ection A.3: Notes, Comments, and Explanations	

### Division for Air Quality

300 Sower Boulevard Frankfort, KY 40601 (502) 564-3999

D	$\mathbf{E}$	Ρ7	70	O	7	١

~	_			_ ~	
Callega	Lim	100	1010	Deati	_
Source :	СШ	155	IOHS	rion	

Section N.1: Emission SummarySection N.2: Stack InformationSection N.3: Fugitive Information

**Buffalo Trace Distillery, Inc.** 

21-073-00009

V-12-056

1373 9/25/2019 \_\_ Section N.4: Notes, Comments, and Explanations

Additional	Documentation	
		•

\_\_ Complete DEP7007AI

Date:			

Agency Interest (AI) ID:

Source Name: KY EIS (AFS) #:

Permit #:

N.1: En	N.1: Emission Summary															
Emission	Emission	Process	Process	Control Device	Control		Maximum Design Capacity		Emission	Emission Factor Source (e.g. AP-42,	Capture	Control	Hourly En	Controlled		Controlled
Unit #	Unit Name	ID	Name	Name	Device ID	Stack ID	(SCC Units/hour)	Pollutant	Factor (lb/SCC Units)	Stack Test, Mass Balance)	Efficiency (%)	Efficiency (%)	Potential (lb/hr)	Potential (lb/hr)	Potential (tons/yr)	Potential (tons/yr)
15	BOILER 11	01	NATURAL GAS COMBUSTION	NA	NA	S15	0.059	PM	7.60	AP-42 Section 1.4 Table 1.4-2 (7/98)	100.00%	0.00%	0.451	0.451	1.97	1.97
								PM10	7.60	AP-42 Section 1.4 Table 1.4-2 (7/98)	100.00%	0.00%	0.451	0.451	1.97	1.97
								PM2.5	7.60	AP-42 Section 1.4 Table 1.4-2 (7/98)	100.00%	0.00%	0.451	0.451	1.97	1.97
								SO2	0.600	AP-42 Section 1.4 Table 1.4-2 (7/98)	100.00%	0.00%	0.036	0.036	0.156	0.156
								NOx	50.0	AP-42 Section 1.4 Table 1.4-1 (7/98)	100.00%	0.00%	2.97	2.97	13.0	13.0
								CO	84.0	AP-42 Section 1.4 Table 1.4-1 (7/98)	100.00%	0.00%	4.98	4.98	21.8	21.8
								VOC	5.50	AP-42 Section 1.4 Table 1.4-2 (7/98)	100.00%	0.00%	0.326	0.326	1.43	1.43
								CO2	119,317	EPA's GHG Reporting Rule (40 CFR 98), Table C-1	100.00%	0.00%	7,077	7,077	30,998	30,998
								CH4	2.25	EPA's GHG Reporting Rule (40 CFR 98), Table C-2	100.00%	0.00%	0.133	0.133	0.584	0.584
								N2O	0.225	EPA's GHG Reporting Rule (40 CFR 98), Table C-2	100.00%	0.00%	0.013	0.013	0.058	0.058
								CO2e	119,440	Scaled GHG by GWP	100.00%	0.00%	7,084	7,084	31,030	31,030
								Total HAPs	1.89	Sum of HAPs, AP-42 Section 1.4 Table 1.4-3 (7/98)	100.00%	0.00%	0.112	0.112	0.491	0.491

							Maximum Design		Uncontrolled	Emission Factor			Hourly Emissions		Annual Emissions	
Emission Unit#	Emission Unit Name	Process ID	Process Name	Control Device Name	Control Device ID	Stack ID	Capacity (SCC	Pollutant	Emission Factor (lb/SCC Units)	Source (e.g. AP-42, Stack Test, Mass Balance)	Capture Efficiency (%)	Control Efficiency	Uncontrolled Potential (lb/hr)	Controlled Potential (lb/hr)	Uncontrolled Potential (tons/yr)	Controlled Potential (tons/yr)
15	BOILER 11	02	GNS COMBUSTION	NA	NA	S15	0.088	PM	3.30	AP-42 Section 1.3 Table 1.3-1 & 2 (5/10)	100.00%	0.00%	0.289	0.289	1.27	1.27
								PM10	3.30	AP-42 Section 1.3 Table 1.3-1 & 2 (5/10)	100.00%	0.00%	0.289	0.289	1.27	1.27
								PM2.5	3.30	AP-42 Section 1.3 Table 1.3-1 & 2 (5/10)	100.00%	0.00%	0.289	0.289	1.27	1.27
								S02	2.13	AP-42 Section 1.3 Table 1.3-1 (5/10)	100.00%	0.00%	0.187	0.187	0.817	0.817
								NOx	20.0	AP-42 Section 1.3 Table 1.3-1 (5/10)	100.00%	0.00%	1.75	1.75	7.67	7.67
								CO	5.00	AP-42 Section 1.3 Table 1.3-1 (5/10)	100.00%	0.00%	0.438	0.438	1.92	1.92
								VOC	0.200	AP-42 Section 1.3 Table 1.3-3 (5/10)	100.00%	0.00%	0.018	0.018	0.077	0.077
								CO2	10,425	EPA's GHG Reporting Rule (40 CFR 98), Table C-1	100.00%	0.00%	913	913	3,998	3,998
								CH4	0.168	EPA's GHG Reporting Rule (40 CFR 98), Table C-2	100.00%	0.00%	0.015	0.015	0.064	0.064
								N2O	0.017	EPA's GHG Reporting Rule (40 CFR 98), Table C-2	100.00%	0.00%	0.001	0.001	0.006	0.006
								CO2e	10,435	Scaled each pollutant by GWP	100.00%	0.00%	914	914	4,002	4,002
								Total HAPs	0.068	Sum of HAPs, AP-42 Section 1.4 Table 1.4-3 (7/98)	100.00%	0.00%	0.006	0.006	0.026	0.026

# Section N.2: Stack Information

# **UTM Zone:**

	Identify all Emission Units (with Process	Stack Physical Data			Stack UTM	Coordinates	Stack Gas Stream Data		
Stack ID	ID) and Control Devices that Feed to Stack	Equivalent Diameter	Height  (ft)	Base Elevation (ft)	Northing (m)	Easting (m)	Flowrate (acfm)	Temperature (°F)	Exit Velocity  (ft/sec)
S15	15	3.75	40	505	4,231,873	686,300	18,766	300	28.3

# Section N.3: Fugitive Information Zone: **Area Physical Data Area UTM Coordinates** Area Release Data Release Release Length of the X Length of the Temperatur Side Height Y Side Northing **Easting** Emission Unit # Emission Unit Name Process ID (ft)(ft) (ft) (m) (m)

11/2018	DEP7007AI
11/2010	DLI /00/M

Section N.4: Notes, Comments, and Explanations									

)18				<b>DEP700</b>	7V		Add	DEP70 itional Documentation				
Division	n for Air Quality	App	licable Re	quirements a	nd Compliance A	Activities	Complet	te DEP7007AI				
300 Se	ower Boulevard		Section	V.1: Emission an	d Operating Limitation	n(s)						
Frank	xfort, KY 40601		Section V.2: Monitoring Requirements									
(50	02) 564-3999		Section V.3: Recordkeeping Requirements									
			Section	V.4: Reporting R	equirements							
			Section	V.5: Testing Req	uirements							
			Section	V.6: Notes, Com	ments, and Explanatio	ns						
Source Name:	Buffal	o Trace Distiller	y, Inc.									
XY EIS (AFS)	#: <u>21-073</u>	-00009										
Permit #:	V-12-0											
Agency Interes		1373										
Date:	9/25/20											
Section V.1:	Emission and	Operating Lin	nitation(s)									
Emission Unit #	Emission Unit Description	Applicable Regulation or Requirement	Pollutant	Emission Limit (if applicable)	Voluntary Emission Limit or Exemption (if applicable)	Operating Re Limit (if app	tation	Method of Determining Compliance with the Emission and Operating Requirement(s)				

EP7007AI

Section V	Section V.2: Monitoring Requirements												
Emission Unit #	Emission Unit Description	Pollutant	Applicable Regulation or Requirement	Parameter Monitored	Description of Monitoring								
15	BOILER 11	N/A	40 CFR 63.11201(b); Table 2 of 40 CFR 63 Subpart JJJJJJ	Energy Efficiency	Conduct a one-time energy assessment in accordance with the requirements of Table 2 of 40 CFR 63 Subpart JJJJJJ.								
15	BOILER 11	N/A	40 CFR 63.11223(b); Table 2 of 40 CFR 63 Subpart JJJJJJ	Tune-up	Conduct biennial tune-ups in accordance with the requirements of Table 2 of 40 CFR 63 Subpart JJJJJJ.								

DEP7007AI

Section V.3: Recordkeeping Requirements								
Emission Unit#	Emission Unit Description	Pollutant	Applicable Regulation or Requirement	Parameter Recorded	Description of Recordkeeping			
15	BOILER 11	N/A	40 CFR 63.11225(c)	General Recordkeeping	Maintain records of the one-time energy assessment, biennial tune-ups, notifications, and compliance reports as required under this section.			
15	BOILER 11	N/A	40 CFR 63.11225(c)(2)(ii)	NHSM Criteria	Because GNS has been determined not to be solid waste pursuant to § 241.3(b)(1), keep a record documenting how the secondary material meets each of the legitimacy criteria under § 241.3(d)(1).			

DEP7007AI

# **Section V.4: Reporting Requirements**

Emission Unit #	Emission Unit Description	Pollutant	Applicable Regulation or Requirement	Parameter Reported	Description of Reporting
15	BOILER 11	N/A	40 CFR 63.11225(a)(2)		File an initial notification within 120 days of becoming subject to the standard (BTD is interpreting the 120-day clock as starting on the date KDAQ provided feedback that Boiler 11 is subject to Boiler NESHAP requirements for oil subcategory boilers because of its GNS combustion).
15	BOILER 11	N/A	40 CFR 63.11225(a)(4)	NOCS	File a Notification of Compliance Status through CEDRI.
15	BOILER 11	N/A	40 CFR 63.11225(b)	Compliance Reports	File ongoing compliance reports biennially.

Section V	Section V.5: Testing Requirements								
Emission Unit #	Emission Unit Description	Pollutant	Applicable Regulation or Requirement	Parameter Tested	Description of Testing				

1/2018	DEP7007A
1/2010	DEI /00/11

Section V.6: Notes, Comments, and Explanations					

**Emission Calculations** 

# B-1. Boiler 11 (EU ID 15) Operating Information

# B-1.1 Boiler Duty and Fuel Consumption Data

<b>Boiler Operating Information</b>	Value	Units	Basis
Rated Heat Input Capacity	60.5 N	/IMBtu/hr	Nameplate heat input rating
Maximum Fuel Usage - NG	0.059 N	/IMscf/hr	= 60.5 MMBtu/hr / 1020 Btu/scf
Maximum Fuel Usage - GNS	Maximum Fuel Usage - GNS 0.088 Mgal/hr		= 60.5 MMBtu/hr*10^6 Btu/MMBtu / 10469 Btu/lb / 6.6 lb/gal*10% - Assuming Maximum of 10% Capacity
Hours Restriction	8,760 h	rs/yr	Continuous annual operations
B-1.1.1 Constants and Conversion Fa	ictors		

Constants	Value Units	Basis
Density of GNS	6.6 lb/gal	lb/gal (assumed based on ethanol)
Heating Value of NG	1,020 Btu/scf	Standard HHV from AP-42 Section 1.4; used in Title V renewal application
Heating Value of GNS	10,469 Btu/lb	Btu/lb (2019 Alcor sampling results, per ASTM D240)
	69.1 MMBtu/Mgal	Calculated
	0.0145 Mgal/MMBtu	Calculated

# B-2. Boiler 11 (EU ID 15) Natural Gas Emission Factors

### **B-2.1 Emission Factor Basis**

### B-2.1.1 Criteria Pollutants Emission Factors

		Emission Factor	Emission Factor	
Pollutant	CAS#	(lb/MMBtu)	(lb/MMscf)	Emission Factor Basis
PM	na	0.0075	7.6	AP-42 Section 1.4 Table 1.4-2 (7/98)
PM-CON				
= PM10-CON	na	0.0056	5.7	AP-42 Section 1.4 Table 1.4-2 (7/98)
= PM25-CON				
PM-FIL	na	0.0019	1.9	AP-42 Section 1.4 Table 1.4-2 (7/98)
PM10	na	0.0075	7.6	PM = PM10
PM10-FIL	na	0.0019	1.9	PM = PM10
PM2.5	na	0.0075	7.6	PM = PM2.5
PM2.5-FIL	na	0.0019	1.9	PM = PM2.5
SO2	07446-09-5	0.0006	0.60	AP-42 Section 1.4 Table 1.4-2 (7/98)
NOx	10102-44-0	0.0490	50.0	AP-42 Section 1.4 Table 1.4-1 (7/98), factor for small (<100 MMBtu/hr)
NOX	10102-44-0	0.0490	50.0	boiler with LNB but no FGR
CO	00630-08-0	0.0824	84.0	AP-42 Section 1.4 Table 1.4-1 (7/98), factor for small boiler
VOC	na	0.0054	5.50	AP-42 Section 1.4 Table 1.4-2 (7/98)

### B-2.1.2 HAP Emission Factors

		Emission Factor	Emission Factor	
Pollutant	CAS#	(lb/MMBtu)	(lb/MMscf)	Emission Factor Basis
Benzene	00071-43-2	2.06E-06	2.1E-03	AP-42 Section 1.4 Table 1.4-3 (7/98)
Dichlorobenzene	00095-50-1	1.18E-06	1.2E-03	
Formaldehyde	00050-0-0	7.35E-05	7.5E-02	
Hexane	00110-54-3	1.76E-03	1.8	
Naphthalene	00091-20-3	5.98E-07	6.1E-04	
Toluene	00108-88-3	3.33E-06	3.4E-03	
Sum of POMs	na	8.65E-08	8.8E-05	
Arsenic	07440-38-2	1.96E-07	2.0E-04	
Cadmium	07440-43-9	1.08E-06	1.1E-03	
Chromium	07440-47-3	1.37E-06	1.4E-03	
Cobalt	07440-48-4	8.24E-08	8.4E-05	
Manganese	07439-96-5	3.73E-07	3.8E-04	
Mercury	07439-97-6	2.55E-07	2.6E-04	
Nickel	07440-02-0	2.06E-06	2.1E-03	
Selenium	07782-49-2	2.35E-08	2.4E-05	
Lead	07439-92-1	4.90E-07	5.0E-04	
Total HAP		0.002	1.888	

### B-2.1.3 GHG Emission Factors

Global Warming Potentials (GWP) of GHGs per 40 CFR 98 Subpart A, Table A-1.

CO2 1 CH4 25 N2O 298

Pollutant	CAS#	Emission Factor (lb/MMBtu)	Emission Factor (lb/MMscf)	Emission Factor Basis	
CO2	00124-38-9	117	119,317	EPA's GHG Reporting Rule (40 CFR 98), Table C-1	
CH4	00074-82-8	2.2E-03	2.25	EPA's GHG Reporting Rule (40 CFR 98), Table C-2	
N2O	10024-97-2	2.2E-04	0.22	EPA's GHG Reporting Rule (40 CFR 98), Table C-2	
CO2e	na	117	119,440	Scaled each pollutant by GWP	

# B-3. Boiler 11 (EU ID 15) GNS Emission Factors

### B-3.1 Emission Factor Basis - Distillate Oil Emission Factors used for GNS

#### B-3.1.1 Criteria Pollutants Emission Factors

> Pollutant levels are expected to be consistent with or less than traditional fuels such as diesel on a heat input basis. As such, emissions from GNS combustion in Boiler 11 are estimated using AP-42 emission factors for the combustion of distillate oil in boilers.

		Emission Factor	Emission Factor	
Pollutant	CAS#	(lb/MMBtu)	(lb/Mgal)	Emission Factor Basis
PM	na	0.0478	3.3	PM-CON + PM-FIL
PM-CON = PM10-CON = PM25-CON	na	0.0188	1.3	AP-42 Section 1.3 Table 1.3-2 (5/10), factor for total condensable particulate matter from No. 2 oil firing
PM-FIL	na	0.0289	2.0	AP-42 Section 1.3 Table 1.3-1 (5/10), factor for small (<100 MMBtu/hr) boiler
PM10	na	0.0478	3.3	PM = PM10
PM10-FIL	na	0.0289	2.0	PM = PM10
PM2.5	na	0.0478	3.3	PM = PM2.5
PM2.5-FIL	na	0.0289	2.0	PM = PM2.5
SO2	07446-09-5	0.0308	2.13	AP-42 Section 1.3 Table 1.3-1 (5/10), using 15 ppmw sulfur as maximum expected from GNS
NOx	10102-44-0	0.2895	20.0	AP-42 Section 1.3 Table 1.3-1 (5/10), factor for small (<100 MMBtu/hr) boiler
CO	00630-08-0	0.0724	5.0	AP-42 Section 1.3 Table 1.3-1 (5/10), factor for small (<100 MMBtu/hr) boiler
VOC	na	0.0029	0.20	AP-42 Section 1.3 Table 1.3-3 (5/10), NMTOC factor for industrial boiler

### B-3.1.2 HAP Emission Factors

> Pollutant levels are expected to be consistent with or less than traditional fuels such as diesel on a heat input basis. As such, emissions from GNS combustion in Boiler 11 are estimated using AP-42 emission factors for the combustion of distillate oil in boilers.

		Emission Factor	Emission Factor	
Pollutant	CAS#	(lb/MMBtu)	(lb/Mgal)	Emission Factor Basis
Formaldehyde	00050-0-0	8.83E-04	6.1E-02	AP-42 Section 1.3 Table 1.3-8 (5/10), max of range
POM	na	4.78E-05	3.3E-03	AP-42 Section 1.3 Table 1.3-8 (5/10)
Arsenic	07440-38-2	4.00E-06	2.8E-04	AP-42 Section 1.3 Table 1.3-10 (5/10)
Beryllium	07440-41-7	3.00E-06	2.1E-04	
Cadmium	07440-43-9	3.00E-06	2.1E-04	
Chromium	07440-47-3	3.00E-06	2.1E-04	
Manganese	07439-96-5	6.00E-06	4.1E-04	
Mercury	07439-97-6	3.00E-06	2.1E-04	
Nickel	07440-02-0	3.00E-06	2.1E-04	
Selenium	07782-49-2	1.50E-05	1.0E-03	
Lead	07439-92-1	9.00E-06	6.2E-04	
Total HAP		0.001	0.068	

#### B-3.1.3 GHG Emission Factors

> CO2, CH4 and N2O emissions for GNS combustion are estimated using the ethanol (biomass fuels-liquid) emission factors established by Tables C-1 and C-2 to 40 CFR 98.

Global Warming Potentials (GWP) of GHGs per 40 CFR 98 Subpart A, Table A-1.

CO2 1 CH4 25 N2O 298

Pollutant	CAS#	Emission Factor (lb/MMBtu)	Emission Factor (lb/Mgal)	Emission Factor Basis
CO2	00124-38-9	151	10,425	EPA's GHG Reporting Rule (40 CFR 98), Table C-1
CH4	00074-82-8	2.4E-03	0.17	EPA's GHG Reporting Rule (40 CFR 98), Table C-2
N2O	10024-97-2	2.4E-04	0.02	EPA's GHG Reporting Rule (40 CFR 98), Table C-2
CO2e	na	151	10,435	Scaled each pollutant by GWP

# B-4. Boiler 11 (EU ID 15) Maximum PTE

> The following evaluation compares emissions from combusting pure natural gas versus co-firing a mix of 90% natural gas and 10% GNS to supply the maximum heat input rate to Boiler 11. The right-hand columns identify the worst-case annual emissions of each pollutant and the corresponding fuel basis.

	PTE - 100% NG		PTE - 90%	/10% Blend	PTE - MAX			
	(lb/hr)	(tpy)	(lb/hr)	(tpy)	(lb/hr)	(tpy)	Basis	
Primary Pollutants								
PM	0.451	1.97	0.695	3.04	0.695	3.04	90%/10% Blend	
PM-CON	0.338	1.48	0.418	1.83	0.418	1.83	90%/10% Blend	
PM-FIL	0.113	0.494	0.277	1.21	0.277	1.21	90%/10% Blend	
PM10	0.451	1.97	0.695	3.04	0.695	3.04	90%/10% Blend	
PM10-FIL	0.113	0.494	0.277	1.21	0.277	1.21	90%/10% Blend	
PM2.5	0.451	1.97	0.695	3.04	0.695	3.04	90%/10% Blend	
PM2.5-FIL	0.113	0.494	0.277	1.21	0.277	1.21	90%/10% Blend	
SO2	3.56E-02	0.156	0.219	0.957	0.219	0.957	90%/10% Blend	
NOx	2.97	13.0	4.42	19.4	4.42	19.4	90%/10% Blend	
CO	4.98	21.8	4.92	21.6	4.98	21.8	100% NG	
VOC	0.326	1.43	0.311	1.36	0.326	1.43	100% NG	
CO2	7,077	30,998	7,282	31,896	7,282	31,896	90%/10% Blend	
CH4	0.133	0.584	0.135	0.590	0.135	0.590	90%/10% Blend	
N2O	1.33E-02	5.84E-02	1.35E-02	5.90E-02	1.35E-02	5.90E-02	90%/10% Blend	
CO2e	7,084	31,030	7,290	31,929	7,290	31,929	90%/10% Blend	
Total HAPs	0.112	0.491	0.107	0.468	0.112	0.491	100% NG	
HAPs/metals								
Benzene	1.25E-04	5.46E-04	na	na	1.25E-04	5.46E-04	100% NG	
Dichlorobenzene	7.12E-05	3.12E-04	na	na	7.12E-05	3.12E-04	100% NG	
Formaldehyde	4.45E-03	1.95E-02	9.34E-03	4.09E-02	9.34E-03	4.09E-02	90%/10% Blend	
Hexane	0.107	0.468	na	na	0.107	0.468	100% NG	
Naphthalene	3.62E-05	1.58E-04	na	na	3.62E-05	1.58E-04	100% NG	
Toluene	2.02E-04	8.83E-04	na	na	2.02E-04	8.83E-04	100% NG	
Sum of POMs	5.23E-06	2.29E-05	2.94E-04	1.29E-03	2.94E-04	1.29E-03	90%/10% Blend	
Arsenic	1.19E-05	5.20E-05	3.49E-05	1.53E-04	3.49E-05	1.53E-04	90%/10% Blend	
Beryllium	na	na	1.82E-05	7.95E-05	1.82E-05	7.95E-05	90%/10% Blend	
Cadmium	6.52E-05	2.86E-04	7.69E-05	3.37E-04	7.69E-05	3.37E-04	90%/10% Blend	
Chromium	8.30E-05	3.64E-04	9.29E-05	4.07E-04	9.29E-05	4.07E-04	90%/10% Blend	
Cobalt	4.98E-06	2.18E-05	na	na	4.98E-06	2.18E-05	100% NG	
Manganese	2.25E-05	9.87E-05	5.66E-05	2.48E-04	5.66E-05	2.48E-04	90%/10% Blend	
Mercury	1.54E-05	6.75E-05	3.20E-05	1.40E-04	3.20E-05	1.40E-04	90%/10% Blend	
Nickel	1.25E-04	5.46E-04	1.30E-04	5.71E-04	1.30E-04	5.71E-04	90%/10% Blend	
Selenium	1.42E-06	6.24E-06	9.20E-05	4.03E-04	9.20E-05	4.03E-04	90%/10% Blend	
Lead	2.97E-05	1.30E-04	8.11E-05	3.55E-04	8.11E-05	3.55E-04	90%/10% Blend	

# **NHSM Evaluation**

# C-1. Non-Hazardous Secondary Material Evaluation for GNS

Table 1. GNS Comparison to Traditional Fuel Oil Contaminant Levels

			Sampling	Results erwise noted	GNS Range	Traditional Fuel Range	GNS within	
Contaminants	<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>	, <u>5</u>	ppmw	ppmw	Traditional Fuel Range?
Non-metal Elements								
Total Sulfur		1.30	2.70	13.80		1.30 - 13.80	ND - 57,000	Yes
Total Fluorine		1.00	1.00	1.00		1.00 - 1.00	ND - 14	Yes
Total Chlorides (chlorine)		1.20	1.26	1.25		1.20 - 1.26	ND - 1,260	Yes
Nitrogen		1.70	1.20	1.50		1.20 - 1.70	42 - 8,950	Yes
Metal Elements								
Mercury	0.02	0.02	0.02	0.02		0.02 - 0.02	ND - 0.2	Yes
Arsenic	0.09	1.00	1.00	1.00		0.09 - 1.00	ND - 13	Yes
Beryllium	0.01	0.20	0.20	0.20		0.01 - 0.20	ND - 19	Yes
Cadmium	0.01	0.20	0.20	0.20		0.01 - 0.20	ND - 1.4	Yes
Chromium	0.01	0.50	0.50	0.50		0.01 - 0.50	ND - 37	Yes
Lead	0.02	1.00	1.00	1.00		0.02 - 1.00	ND - 56.8	Yes
Manganese	0.08	0.50	0.50	0.50		0.08 - 0.50	ND - 3,200	Yes
Nickel	0.04	1.00	1.00	1.00		0.04 - 1.00	ND - 270	Yes
Selenium	0.07	1.00	1.00	1.00		0.07 - 1.00	ND - 4.0	Yes
Total Volatile HAP <sup>b,c</sup>								
Acetaldehyde					1.90	1.90 - 1.90		
Methanol					1.90	1.90 - 1.90		
Total Volatile HAP					3.79	3.79 - 3.79	6,072 - 19,810	Yes

<sup>&</sup>lt;sup>a</sup> The *Traditional Fuels Range* column presents expected contaminant concentration ranges for traditional fuel oil. These summary statistics were developed by EPA "as a service to assist non-hazardous secondary materials processors and combustors making contaminant comparisons" and can be found at <a href="https://www.epa.gov/rcra/contaminant-concentrations-traditional-fuels-tables-comparison">https://www.epa.gov/rcra/contaminant-concentrations-traditional-fuels-tables-comparison</a> (November 29, 2011). These ranges are also presented in EPA's 2018 final rule entitled **Additions to List of Categorical Non-Waste Fuels: Other Treated Railroad Ties [EPA-HQ-OLEM-2016-0248; FRL-9969-80-OLEM]**. The final rule supplements these summary statistics with "SVOC values from 2013 IEc data that will be available in the rule docket."

b Acetaldehyde and methanol are both volatile HAPs based on Table 8. Compounds Considered Contaminants -- With Group Information to the 2011 NHSM rule [Federal Register /Vol. 76, No. 247 / Friday, December 23, 2011 / Proposed Rules / pg. 80479]

<sup>&</sup>lt;sup>c</sup> The method detection limit was converted from mg/L to a ppmw basis using an assumed density for GNS (based on the density of ethanol).

### Table 2. GNS Comparison to Federal TSM, Hq, and CI Limits (Not Directly Applicable to Boiler 11)

- > As an area source of HAP emissions, Buffalo Trace's Frankfort distillery boilers combusting GNS are NOT subject to 40 CFR 63 Subpart DDDDD (Boiler MACT). Instead, these boilers are subject to 40 CFR 63 Subpart JJJJJJ (Boiler NESHAP); however, the Boiler NESHAP regulation does not establish limits for mercury (Hg), chlorine (Cl), or Total Selected Metals (TSM) for liquid fuel-fired boilers. Therefore, the Boiler MACT regulatory limits are used as surrogates for the limits satisfied by traditional fuels for the purpose of designating the Grain Neutral Spirits (GNS) stream as a Non-Hazardous Secondary Material (NHSM).
- > Under the Boiler NESHAP regulation, liquid fuel "includes, but is not limited to, light liquid, heavy liquid, any form of liquid fuel derived from petroleum, used oil, liquid biofuels, biodiesel, and vegetable oil."
- > The Boiler NESHAP regulation defines *light liquid* as including "distillate oil, biodiesel, or vegetable oil", where:
  - 1. Biodiesel is defined as "a mono-alkyl ester derived from biomass and conforming to ASTM D6751-11b".
- 2. Distillate oil is defined as a fuel stream that complies with the specifications for fuel oil numbers 1 and 2 (per ASTM D396 or D975), kerosene, or biodiesel (per ASTM D6751-11b).
- 3. Vegetable oil is defined as "oils extracted from vegetation."
- > Buffalo Trace's GNS stream is not a mono-alkyl ester, distillate oil, or vegetable oil. Although it is produced from vegetation, its production involves fermenting the vegetation to produce alcohol, then filtering and distilling the resulting alcohol as opposed to extracting oil directly. Furthermore, this stream is not considered biomass, as that term is limited to bio-based solid fuels under the Boiler MACT regulation.
- > As a liquid biofuel that does not meet the definition of light liquid, it would most likely be classified as a *heavy liquid*, which is defined as "residual oil and any other liquid fuel not classified as a light liquid." For conservatism, the following table evaluates whether the distillery would achieve compliance with the Boiler MACT limits for both light and heavy liquid fuel-fired boilers, if this regulation were applicable to Buffalo Trace's Frankfort distillery.

	GNS Sampling Results <sup>a</sup>					Pure GNS As Combusted		Boiler MACT Limits	
	1	2	3	4	Average	100% GNS <sup>b</sup>	90% NG/10% GNS Blend <sup>c</sup>	Existing Heavy Liquid	Existing Light Liquid
Pollutant	ppmw	ppmw	ppmw	ppmw	ppmw	lb/MMBtu	lb/MMBtu	lb/MMBtu	lb/MMBtu
Mercury	0.0200	< 0.02	< 0.02	< 0.02	0.02	1.91E-06	1.91E-07	2.0E-06	2.0E-06
Total Selected Metals (TSM)	0.3241	5.40	5.40	5.40	4.13	3.95E-04	3.95E-05	2.0E-04	6.2E-05
Arsenic	0.0895	< 1.00	< 1.00	< 1.00	0.77				
Beryllium	0.0114	< 0.20	< 0.20	< 0.20	0.15				
Cadmium	0.0095	< 0.20	< 0.20	< 0.20	0.15				
Chromium	0.011	< 0.50	< 0.50	< 0.50	0.38				
Lead	0.017	< 1.00	< 1.00	< 1.00	0.75				
Manganese	0.0762	< 0.50	< 0.50	< 0.50	0.39				
Nickel	0.0381	< 1.00	< 1.00	< 1.00	0.76				
Selenium	0.0714	< 1.00	< 1.00	< 1.00	0.77				
Total Chlorides <sup>e</sup>		1.20	1.26	1.25	1.24	1.21E-04	1.21E-05	1.10E-03	1.10E-03

#### Constants

GNS Net Heat of Combustion 10,469 Btu/lb (Alcor results, per ASTM D240)

GNS Density 6.6 lb/gal (assumed based on ethanol)

- <sup>a</sup> For non-detect results, the method detection limit is used. These non-detect results are denoted by *italicized font*.
- <sup>b</sup> For comparative purposes, the sampling results are converted from ppm to lb/MMBtu using the heating value of GNS.
- <sup>c</sup> Pure GNS is not combusted in Buffalo Trace's facility boilers. Rather, the GNS stream is co-fired with natural gas at a ratio of approximately 5% GNS to 95% gas on a heat input basis. For conservatism, the pollutant concentrations in a 10% GNS to 90% gas mixture are compared to the Boiler MACT limits.
- d The Boiler MACT limit applies to HCI; therefore, the lb/MMBtu emission factor for total chlorides is multiplied by 1.028, which is the stoichiometric conversion between chlorides and HCI. The Sample 1 non-detect result is omitted from the averaging calculations, as discussed in Table 1.